# PRODUCT DATA SHEET



### **LITHIUM BASE ALL PURPOSE GREASES**

#### **AP-2, AP3 & AP3 (RED)**

These are multifunctional all-purpose lithium-based greases. These greases possess excellent shear stability, high load carrying properties & prevent welding & seizure of moving parts under shock loading conditions. These greases are recommended for industrial & automotive, earth moving equipment, gear couplings, electric motors, ball & roller bearings etc.

## **PRODUCT FEATURES**

- High drop point.
- Excellent thermal and structural stability.
- Optimum lubrication under even adverse mechanical conditions.
- Good surface adhesion.
- ❖ Gives excellent protection against rust, corrosion and water wash out.

#### **APPLICATIONS**

- Plain and anti-friction bearings of cars, commercial Vehicles etc.
- Heavy duty ball and roller bearings of steel rolling mills, textile mills, papers mills, sugar mills etc.
- Universal joints and spline shafts.
- ❖ Suitable for bearings operating at temperature up to 130°C.

### **PERFORMANCE LEVEL**

❖ IS 12203-1999 (Reaffirmed 2019), AP2: NLGI -2 & AP3: NLGI -3 specifications.

	CHARACTERISTICS			
S. NO.	PROPERTIES	AP-2	AP-3	AP-3 (RED)
1.	Appearance	Light yellow	Light yellow	Red
2.	Consistency of worked grease, @ 25±0.5°C, 0.1mm units (60 double strokes)	265-280	220-250	220-250
3.	Drop Point, °C, min.	180	180	180
4.	Soap Type	Lithium	Lithium	Lithium
5.	Structure	Smooth & buttery	Smooth & buttery	Smooth & buttery

<sup>\*</sup>The specifications are subject to variations/development/customization.

## **PACKINGS:**

**AP-2:** 180kg, 18kg

AP-3 & AP-3 (RED): 180kg,18kg,10kg, 5kg, 3kg, 2kg,1kg, 500g, 200g,100g,50g