PRODUCT DATA SHEET



SEMI SYNTHETIC ENGINE OIL LEOPARD – 5W30

LEOPARD 5W30 is a cost-effective Semi – Synthetic Crank Case lubricant manufactured through oils produced by isomerization & hydro cracking process. It contains a balanced combinations of modern performance additives like antioxidants, VI Improvers, Anti-wear, Extreme Pressure (EP) & metal deactivators which protects the engine against sludge & deposits. Its high viscosity index & low pour point provides optimum viscosity & fluidity across a wide range of temperatures.

PRODUCT FEATURES

- High viscosity index
- Very good oxidation / thermal stability
- ❖ High level of detergency / dispersancy
- Easy Engine start ability

BENEFITS

- Good wear protection against wide operating conditions
- ❖ Protect the Engine components from sludge, rust & corrosion
- Lower friction of the moving & rubbing parts
- Longer Service life

RECOMMENDED for modern-day high-performance cars running on Petrol / Diesel / CNG like Tata Motors, Hyundai Motors, Maruti, Datsun, Toyata, BMW, GM, Chevrolet, Ford etc.

PERFORMANCE LEVEL: Meets API SM/CF Grade performance level requirements.

CHARACTERISTICS		
S.NO.	PROPERTIES	LEOPARD – 5W30
1.	Appearance	Clear Golden Natural
2.	Kinematic Viscosity cSt @ 100°C	10.5 – 12.5
3.	Viscosity Index VI, Min.	135
4.	Flash Point, °C COC, Min	210
5.	Pour Point, °C, Max.	-36
6.	TBN,mg KOH/gm.	6-8

^{*}The specifications are subject to variations/development/customization.

PACKING: 210L, 50L, 3.5L, 1L