

PRODUCT DATA SHEET



COMPRESSOR OILS

PALCOMP C - 100,150,220,320

These are specially developed compressor oils to provide satisfactory lubrication under prolonged high temperature & load conditions. These are formulated with selected base stocks & special compounding agent to give excellent resistance to washing effect of water. These are further fortified with antirust & anticorrosion agent & have good fluidity at low temperature.

PRODUCT FEATURES

- ❖ Excellent oxidation & thermal stability.
- ❖ Resistance to washing effect of water.
- ❖ Good anti wear properties
- ❖ Excellent lubrication of cylinder liners, piston valves.

Recommended for cylinder lubrication of single & multistage compressors handling moist air. **PALCOMP C are not recommended for crankcase lubrication**

PERFORMANCE LEVEL: DIN 51506 specifications.

CHARACTERISTICS					
S. NO.	PROPERTIES	PALCOMP C			
		100	150	220	320
1.	Appearance	Clear, bright colour			
2.	Kinematic Viscosity, cSt @40°C	90-110	140-160	200-240	300-340
3.	Viscosity Index, min.	90	80	80	80
4.	Flash Point, COC, °C, min.	180	180	200	200
5.	Saponification number, KOH/g	2.5-5.0	2.5-5.0	2.5-5.0	6-10

*** The specifications are subject to variations/ development / customization.**

PACKING: 210L, 50L, 20L